

TIGER Neo

48HL4M-DV

450-475

2

¿

48HL4M-DV 1762mm×1134mm フット

	N
	96 (48 × 2)
	1762 × 1134 × 30 mm
	24.0 kg
	2.0mm
	2.0 mm,
	IP68
	Class II
IEC	Class C
	JK03M/JK03M2/ *
	4.0mm ²
	400mm, 200mm

* MC4 MC4-EVO2

	1792 × 1140 × 1249 mm
(2 = 1)	37 / , 74 / , 962 /40

(STC)

(Pmax) [Wp]	450	455	460	465	470	475
(Vmp) [V]	30.04	30.28	30.51	30.74	30.97	31.19
(Imp) [A]	14.98	15.03	15.08	15.13	15.18	15.23
(Voc) [V]	35.91	36.08	36.25	36.42	36.59	36.76
(Isc) [A]	15.73	15.78	15.83	15.88	15.93	15.98
(STC) [%]	22.52	22.77	23.02	23.27	23.52	23.77
	0 ~ + 3 %					
(Pmax)	-0.29 %/°C					
(Voc)	-0.25 %/°C					
(Isc)	0.045 %/°C					

STC: 1000W/m², 25 ,AM=1.5

	-40 °C ~ +70 °C
	1500 VDC (IEC)
	30 A

