

□ □ □ □ □ %

215: 2021 / IEC61730: 2023  
701 / IEC62716 / IEC60068 / IEC62804  
01:2015,  
001:2015,  
001:2018,



495-520 ワット

|     |                                    |
|-----|------------------------------------|
|     | N                                  |
|     | 204 (51 ÷ 4)                       |
|     | 1906 ÷ 1134 ÷ 30 mm                |
|     | 23.0 kg                            |
|     | 1.6mm                              |
|     | 1.6 mm                             |
|     |                                    |
|     | IP68                               |
|     | Class II                           |
| IEC | Class C                            |
|     | JK03M/JK03M2/ *                    |
|     | 4.0mm <sup>2</sup><br>600mm, 400mm |

\* MC4-EVO2

|          |                          |
|----------|--------------------------|
|          | 1981 × 1140 × 1249 mm    |
| (2 = 1 ) | 37 / , 74 / ,<br>888 /40 |

(STC)

|             |            |
|-------------|------------|
| (Pmax) [Wp] |            |
| (Vmp) [V]   |            |
| (Imp) [A]   |            |
| (Voc) [V]   |            |
| (Isc) [A]   |            |
| (STC) [%]   |            |
|             | 0 ~ + 3 %  |
| (Pmax)      | -0.26 %/°C |
| (Voc)       | -0.24 %/°C |
| (Isc)       | 0.046 %/°C |

STC: 1000W/m<sup>2</sup>, 25 ,AM=1.5

|  |                |
|--|----------------|
|  |                |
|  | 1500 VDC (IEC) |
|  | 30 A           |

(W)

- (51QL6-DV 505W

(V)

- (51QL6-DV 505W

⊕

(V)